

**KX-TEA308E**

Advanced Hybrid Telephone System

3 CO Lines and 8 Extensions

Efficient Call Handling

Day/Night/Lunch Mode

Caller ID Display

Voice Message (Optional)

Easy Programming/Maintenance



Advanced Hybrid Telephone System

System Capacity (max.)

<b>Operator</b>	1.0
<b>System Speed Dialling</b>	100.0
<b>Personal Speed Dialling</b>	10 / Ext.
<b>One-Touch Dialling</b>	Max 12 / Ext.
<b>Extension Groups</b>	8.0
<b>UCD Group</b>	1.0
<b>Toll Restriction Levels</b>	5.0
<b>Account Codes (Verified)</b>	50.0
<b>Call Park</b>	10.0
<b>Call Log (Caller ID)</b>	20 (Personal) 300 (Common)
<b>Absent Messages</b>	6.0
<b>Message Waiting</b>	8 / Ext.
<b>Emergency Codes</b>	5.0
<b>External Music Source</b>	1.0
<b>External Pager</b>	1.0
<b>Doorphones</b>	2.0
<b>Door Openers</b>	2.0
<b>DSS Consoles</b>	2.0
<b>Outgoing Message (DISA)</b>	180 sec

**Outgoing Message (BV)** 125 messages or 60 min. (/1 ch)

---

### Connectors

---

**CO Line** yes

---

**Intercom** yes

---

**Paging Output** yes

---

**External Music** yes

---

**SMDR** yes

---

**Programming** yes

---

### Features

---

**Maximum Capacity** 3COs

---

**Intercom Paths** 3.0

---

**Dialling Method** External: Tone (DTMF) / Pulse (10 pps, 20 pps)  
Internal: Tone (DTMF) / Pulse (10 pps, 20 pps)

---

**Dialling Conversion** Pulse to DTMF

---

**Polarity Reverse Detection** yes

---

**Voice Mail Ports** 2 ports (APT or DTMF)

---

**DTMF Receivers** 2.0

---

**DTMF Generator** 1.0

---

**Power Failure Transfer Ports** 1.0

---

**Direct Connection to External Battery** yes

---

### General Data

---

**Power Source** AC 100 - 240 V, 50/60 Hz

---

**Power Consumption** 34W

---

### Dimensions (mm)

---

**Width** 249.0

---

**Height** 316.0

---

**Depth** 73.0

---

**Weight (when fully expanded)** 1

---